



R A P I D R O A D R E P A I R

PO Box 3056, Northriding, 2162

Tel: 010-590-3329

[www.repairroads.com](http://www.repairroads.com)

A new generation  
Cold Asphalt



# repair<sup>®</sup>

## is an easy to use, instant and permanent solution to repairing potholes and roads

### repair<sup>®</sup> unique formula

The **repair<sup>®</sup>** formula contains five highly specialised additives, quality penetration grade bitumen and specially selected aggregates.

To meet the high Internationally accepted specification the product is manufactured in a controlled environment with extremely strict levels of quality control.

### repair<sup>®</sup> comparisons

	repair <sup>®</sup>	Hot Asphalt	Standard Cold
Permanent	✓	✓	✗
Works in water	✓	✗	✗
No tack coat	✓	✓	✓
No bleeding	✓	✗	✗
Trafficable immediately	✓	✗	✗
Operational versatility	✓	✗	✓

### repair<sup>®</sup> versatility

- Instant and permanent repair to potholes of any size/shape/depth.
- Infilling cable ducts, trenches and as a joint filler.
- Repairs to concrete, slab corners, cut outs, spalls.
- Reinstatement around manhole covers, landing lights, cats eyes, etc. (bonds well to metal/composite materials).
- Bridge deck and core hole repairs, ramping, construction of speed humps, rumble strips and complete surface overlays.
- Specified for motorways, aircraft runways, docks, highways, rail platforms, car parks, public utilities, etc.
- Used by all types of industry, builders and home owners.



### repair<sup>®</sup> benefits include

Easy and instant application.

Can be applied in all weather conditions.

Maximum workability even in cold operating conditions.

Proven life of repairs, a minimum of 10 years.

### repair<sup>®</sup> simple to use



1. Brush out loose debris/water/oil from ANY shape hole.



2. Simply tip **repair<sup>®</sup>** from the pack (to a maximum of 30mm) and compact. Deeper holes require layering  $\pm 30$ mm and compacting at each stage.



3. For small areas compact to road level using hand tamper. Areas larger than half m<sup>2</sup> use a mechanical vibrating roller/plate compactor. If underfilled tip on more **repair<sup>®</sup>** and compact to level. Keep compactor wet with water to avoid sticking to material.



4. On completion of repair open immediately to traffic.



RAPID ROAD REPAIR